# **Specifications**

# M - Super Compact 6 5 kW - 230 V / 50 Hz version Art. No. 41102005



GENERAL INFORMATION	
Nominal power	5 kW (peak power capability: 200%)
Nominal voltage	230 V
Output frequency	50 Hz
Power factor/cos phi	1
Voltage tolerance (V)	±5%
Frequency tolerance (Hz)	±5%
Voltage regulation	Capacitor
Starter battery (optional)	12 V / 85 Ah
Battery charge current	auxiliary winding 4 A
Dimensions including sound shield (L $x$ W $x$ H)	690 x 525 x 580 mm
Dry weight	178 kg
Wet marine exhaust	Ø 40 mm
Dry exhaust pipe	Ø 1 inch BSP
Location oil refill cap	top & side
Max. operation angle	25° in all directions
Alternator	water-cooled, no brushes, synchronous
Audible noise level	56.2 dBA (at 7 mtrs)
SPECIFICATIONS DIESEL ENGINE	
Engine model	L2E
	L2E 2
Engine model Number of cylinders Cylinder capacity	2 635 cc
Engine model Number of cylinders	2 635 cc 2x 76 x 70 mm
Engine model Number of cylinders Cylinder capacity	2 635 cc
Engine model Number of cylinders Cylinder capacity Bore & stroke Air consumption Engine cooling	2 635 cc 2x 76 x 70 mm 0.95 m <sup>3</sup> /min indirect water-cooled
Engine model Number of cylinders Cylinder capacity Bore & stroke Air consumption	2 635 cc 2x 76 x 70 mm 0.95 m <sup>3</sup> /min
Engine model Number of cylinders Cylinder capacity Bore & stroke Air consumption Engine cooling Fuel consumption (no load-full load)	2 635 cc 2x 76 x 70 mm 0.95 m <sup>3</sup> /min indirect water-cooled
Engine model Number of cylinders Cylinder capacity Bore & stroke Air consumption Engine cooling Fuel consumption (no load-full load) ACCESSORIES	2 635 cc 2x 76 x 70 mm 0.95 m <sup>3</sup> /min indirect water-cooled 1-2.5 l/hour
Engine model Number of cylinders Cylinder capacity Bore & stroke Air consumption Engine cooling Fuel consumption (no load-full load) ACCESSORIES Remote control panel (standard included)	2 635 cc 2x 76 x 70 mm 0.95 m <sup>3</sup> /min indirect water-cooled 1-2.5 l/hour Digital Diesel Control (DDC) Interface-to-bus optional
Engine model Number of cylinders Cylinder capacity Bore & stroke Air consumption Engine cooling Fuel consumption (no load-full load) <b>ACCESSORIES</b> Remote control panel (standard included) Second remote control panel / slave	2 635 cc 2x 76 x 70 mm 0.95 m <sup>3</sup> /min indirect water-cooled 1-2.5 l/hour Digital Diesel Control (DDC) Interface-to-bus optional Digital Diesel Control (DDC)
Engine model Number of cylinders Cylinder capacity Bore & stroke Air consumption Engine cooling Fuel consumption (no load-full load) <b>ACCESSORIES</b> Remote control panel (standard included) Second remote control panel / slave System panel 7 inch "Touch"	2 635 cc 2x 76 x 70 mm 0.95 m <sup>3</sup> /min indirect water-cooled 1-2.5 l/hour Digital Diesel Control (DDC) Interface-to-bus optional Digital Diesel Control (DDC) Optional
Engine model Number of cylinders Cylinder capacity Bore & stroke Air consumption Engine cooling Fuel consumption (no load-full load) <b>ACCESSORIES</b> Remote control panel (standard included) Second remote control panel / slave System panel 7 inch "Touch" Power Take Off (PTO)	2 635 cc 2x 76 x 70 mm 0.95 m <sup>3</sup> /min indirect water-cooled 1-2.5 l/hour Digital Diesel Control (DDC) Interface-to-bus optional Digital Diesel Control (DDC) Optional n/a
Engine model Number of cylinders Cylinder capacity Bore & stroke Air consumption Engine cooling Fuel consumption (no load-full load) <b>ACCESSORIES</b> Remote control panel (standard included) Second remote control panel / slave System panel 7 inch "Touch" Power Take Off (PTO) Three phase version	2 635 cc 2x 76 x 70 mm 0.95 m <sup>3</sup> /min indirect water-cooled 1-2.5 l/hour Digital Diesel Control (DDC) Interface-to-bus optional Digital Diesel Control (DDC) Optional n/a n/a
Engine model Number of cylinders Cylinder capacity Bore & stroke Air consumption Engine cooling Fuel consumption (no load-full load) <b>ACCESSORIES</b> Remote control panel (standard included) Second remote control panel / slave System panel 7 inch "Touch" Power Take Off (PTO) Three phase version Keel cooling / mobile version	2 635 cc 2x 76 x 70 mm 0.95 m <sup>3</sup> /min indirect water-cooled 1-2.5 l/hour Digital Diesel Control (DDC) Interface-to-bus optional Digital Diesel Control (DDC) Optional n/a n/a See mobile / domestic program
Engine model Number of cylinders Cylinder capacity Bore & stroke Air consumption Engine cooling Fuel consumption (no load-full load) <b>ACCESSORIES</b> Remote control panel (standard included) Second remote control panel / slave System panel 7 inch "Touch" Power Take Off (PTO) Three phase version Keel cooling / mobile version Ungrounded version (insulated return)	2 635 cc 2x 76 x 70 mm 0.95 m <sup>3</sup> /min indirect water-cooled 1-2.5 l/hour Digital Diesel Control (DDC) Interface-to-bus optional Digital Diesel Control (DDC) Optional n/a n/a See mobile / domestic program Art. no. 41102006
Engine model Number of cylinders Cylinder capacity Bore & stroke Air consumption Engine cooling Fuel consumption (no load-full load) <b>ACCESSORIES</b> Remote control panel (standard included) Second remote control panel / slave System panel 7 inch "Touch" Power Take Off (PTO) Three phase version Keel cooling / mobile version	2 635 cc 2x 76 x 70 mm 0.95 m <sup>3</sup> /min indirect water-cooled 1-2.5 l/hour Digital Diesel Control (DDC) Interface-to-bus optional Digital Diesel Control (DDC) Optional n/a n/a See mobile / domestic program

# INSTALLATION ACCESSORIES

Water inlet kit consisting of: Water strainer, hoses, hose clamps, through-hull fitting and seacock.
Art. no. 40230211 Water inlet kit 20 mm (<sup>3</sup>/<sub>4</sub>") - wet exhaust
Syphon breaker kit consisting of: Syphon breaker, hoses, and hose clamps
Art. no. 40230273 Syphon breaker kit 20 mm (<sup>3</sup>/<sub>4</sub>") - wet exhaust
DELTA Exhaust kit consisting of: Exhaust silencer/waterlock with unique rotating connections,

through-hull fitting, hoses and hose clamps

Art. no. 40230251 DELTA Exhaust kit 40 mm (15/8") - wet exhaust

DELTA Water/gas separator kit consisting of: Water/gas separator with unique rotating connections,

through-hull fitting, hoses, hose clamps and seacock

Art. no. 40230261 DELTA Water-gas separator kit 40 mm (1<sup>5</sup>/8")

# Base plate kit

Art. no. 40230209 Base plate kit (includes art. No. 40230217)

Art. no. 40230217 Anti-vibration mounts, up to 280 kg

### Boxcooler kit

Art. no. 40201303 Boxcooler kit 1" - keelcooling

Dry Exhaust kit contains two silencers: an absorption and a resonance muffler including fitting material

Art. no. 40201320 Dry exhaust kit 1" - keelcooling

#### Fuel kit for marine use

Art. no. 40230205 Fuel kit for the M-SC and M-SQ generator systems

#### Starter Batteries for marine use

Art. no. 40290100 AGM starter battery kit S4, 2L, 12 V, 50 Ah, CCA 815 A

**Service kits marine use** are available for maintenance or to have the essential parts at hand. The A-kits include filters and V-belts. Our B-kits are more extensive, including seals and various mechanical parts.